



Overview

It is consisting of high quality 3 strand wire solid Polyester in Ø2,5mm with M5 threaded interchangeable terminals. The terminals are from nickel-plated brass rod with outer diameter Ø7mm

Construction

Its reinforced eyelet in Ø7mm with special formation, facilitates excellent tying of cables

Usage

- Excellent tool for building installations and pipes up to Ø50mm.
- Use lubricant and rubber pulling grip for maximum efficiency.
- Apply some common glue on the thread of terminals for safety during usage.
- The special braid of “3 strand wire” provides excellent penetration, especially in installations of high complexity (corners).
- Suggested lengths: 15m,20m,30m

Notes

The inner product diameter is 450mm. All products are also available in a Ø50mm plastic tube by adding “t” to the product code.

Technical Specifications

Color	orange
Material	3 strand wire of Ø2mm Polyester
Tolerance	±0.2mm
Min. bending radius	25mm
Breaking Strength	up to 250kg
Pulling strength	up to 225kg

Available lengths – Fixed terminals (art.no.)

10 m	— AKAT241
15 m	— AKAT242
20 m	— AKAT243
30 m	— AKAT244
40 m	— AKAT245

Available lengths – Interchangeable terminals (art.no.)

10 m	— AKAT341
15 m	— AKAT342
20 m	— AKAT343
30 m	— AKAT344
40 m	— AKAT345



Min. bending radius
25mm



Pulling strength
Up to 225kg