



Overview

Fiberglass duct rodder Ø11mm with PP outer coating spooled in medium black electrostatic powder coating steel cage Ø890mm.

Construction

It comes with threaded starting/ending joints M12 and interchangeable threaded eyelet M12 (AKAT125). The medium metallic reel Ø890mm offers greater flexibility in transport and storage. It comes with embedded break for quick and easy usage.

Usage

Ideal tool for industrial usage & underground cable laying and pipes from Ø63mm to Ø200mm. It is used as a driver for long distances and it is specifically designed for power cables, telecommunication and fiber optic cables. Operates in horizontal and vertical position. Two rod-out guides, giving ability to work in 2 directions.

Notes

- Apply some light glue at the interchangeable terminals for safety before usage.
- Apply cable lubricant for maximum efficiency during installation.
- Pay attention at the safety instructions and manual, before using the tool.

Technical Specifications

Color	blue
Material	fiberglass core with PP outer coating
Tolerance	±0.2mm
Min. bending radius	Type1 - 400mm Type2 - 220mm
Breaking Strength	up to 6900kg
Pulling strength	up to 500kg
Pipe diameter Ø	63mm-200mm

Available lengths (art.no.)

- 100 m — AKAT056s
- 120 m — AKAT057s
- 150 m — AKAT058s

